




- 1) Charge Controller
- 3) Circuit breakers
- 6) Din Rail mountable Power Terminal Blocks
- 1) Wiring Kit – Assembly pre-wiring and #10AWG Batt-Reg cable
- 1) Backplate



Online Solar, LLC

642 Ponte Villa South

Baltimore, MD 21230



Tel: +1.888.680.2427

Fax: +1.410.528.9445




12 VOLT SYSTEMS

Terminal block can accommodate up to 4 modules // 4 batteries




- NOTES :
- * ALL METAL SURFACES TO BE GROUNDED. SEE :NEC 250.122 FOR DETAILS.
 - * FOLLOW OPERATORS MANUAL GUIDELINES FOR START UP PROCEDURE.





- Quick Start for Solar System**
- * Start with all breakers in OFF position.
 - * Check connections for tightness and correct polarity.
 - * Turn the battery breaker ON first. Isolar breaker ON.
 - * Verify voltages for battery.
 - * Turn the PV breaker ON second.
 - * Verify charging amps.
 - * Proceed to turn the load breaker ON.
- The system should then be operating normally.

- To change batteries or check system components :**
- * Turn the solar breaker OFF first.
 - * Turn the load breaker OFF second.
 - * Turn the battery breaker OFF last.

The system is now de-energized and components may be changed without risk of sparks. Remember however, the battery remains charged and capable of dangerous sparks or arcs if shorted. Neither a battery nor a sunlit solar module can be de-energized, only disconnected.




Online Solar, LLC
 642 Ponte Villa South
 Baltimore, MD 21230
 Tel: +1.888.680.2427
 Fax: +1.410.528.9445



NOTES :

- * ALL METAL SURFACES TO BE GROUNDED. SEE NEC 250.122 FOR DETAILS.
- * FOLLOW OPERATORS MANUAL GUIDELINES FOR START UP PROCEDURE.



Quick Start for Solar System

- * Start with all breakers in OFF position.
 - * Check connections for tightness and correct polarity.
 - * Turn the battery breaker ON first. Isolar breaker ON.
 - * Verify voltages for battery.
 - * Turn the PV breaker ON second.
 - * Verify charging amps.
 - * Proceed to turn the load breaker ON.
- The system should then be operating normally.

To change batteries or check system components :

- * Turn the solar breaker OFF first.
- * Turn the load breaker OFF second.
- * Turn the battery breaker OFF last.

The system is now de-energized and components may be changed without risk of sparks. Remember however, the battery remains charged and capable of dangerous sparks or arcs if shorted. Neither a battery nor a sunlit solar module can be de-energized, only disconnected.

