

# 8A27

## SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	106Ah
Capacity at C/20	92Ah
Weight	63 (28.6 kg)
Plate Alloy	Lead Calcium
Posts	Forged terminals & bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) – 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.40 - 2.43 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing (2 PSI operation)
Resistance	3.0 Milliohms (full charge)
Terminal	T835

Rated non-spillable by ICAO, IATA and DOT

Made in the U.S.A by East Penn Manufacturing

Distributed by:


Valve-Regulated, Absorbed Glass Mat Technology



## DIMENSIONS

Length (mm)	12.75 (324 mm)
Width (mm)	6.88 (175 mm)
Height (mm)	8.63 (220 mm)

## Cycling Ability



Number of cycles vs. depth of discharge at +20°C discharge with 20 hour rate

## MK Battery

1645 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

