



### Main

Range of product	XW
Device short name	XW SCP
Product or component type	System control panel
Product specific application	System configuration and diagnostic information
Control type	4 tactile keypad buttons

### Complementary

Product compatibility	XW system devices
Display type	Backlit LCD screen
Display resolution	128 x 64 pixels
Function available	Internal clock keeps time for the entire system Audible alarm when a fault condition arises Low power consumption
Local signalling	1 LED green for online 1 LED red for fault
Data backed up	Non-volatile memory
Communication port protocol	Xanbus
Provided equipment	Mounting hardware
Device mounting	Flush Surface
Height	152 mm
Width	103 mm
Depth	40 mm
Product weight	0.207 kg

### Environment

Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...85 °C
Standards	CSA C22.2 No 107.1-01
Product certifications	CSA FCC Class B Industry Canada
Marking	CE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.