

# SLP070-12U

## High Efficiency Multicrystalline PV Module

Electrical Characteristics	SLP070-12U
Product code	070011203A
Maximum power (Pmax)	70W
Voltage at Pmax (Vmp)	17.2V
Current at Pmax (Imp)	4.07A
Open-circuit voltage (Voc)	21.6V
Short-circuit current (Isc)	4.35A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	± 5%


\*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

\*NOCT: Nominal operating cell temperature (the data is only for reference)



### Module Diagram


Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]



### Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

### Characteristics



SLP070-12U I-V Curves

Specifications	SLP070-12U
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	774mm[30.47in.]x675mm[26.57in.]x30mm[1.18in.]
Weight	6.00kg[13.22lbs]
Packing information(Carton)	815mm[32.09in.]x715mm[28.15in.]x80mm[3.15in.]/(2pcs/ctn)

\*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

\*Specifications are subject to change without notice at any time.