

HEAVY DUTY MODIFIED SINE WAVE INVERTERS (1750/3000/5000)

CATEGORY:

MODIFIED SINE WAVE
INVERTERS

MODEL RANGE:

GP-1750HD
GP-3000HD
GP-5000HD



GP-1750HD




GP-3000HD



GP-5000HD

IDEAL FOR:



**1 YEAR
WARRANTY**

GP-1750HD / GP-3000HD / GP-5000HD

Run standard AC devices wherever you go. Go Power!'s new Heavy-Duty Modified Sine Wave Inverters bring reliable power to your RV, boat, truck, or even your home if the power goes out.

KEY FEATURES



AC POWER FOR OPTIMAL
PERFORMANCE



EASY TO INSTALL



WIDE VOLTAGE RANGE



USB CONNECTIVITY



FULL OVERLOAD
PROTECTION



HEAVY-DUTY STEEL CASE



CONFORMS TO
UL STD. 458
CERTIFIED TO
CSA STD.
C22.2 No. 107



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3

SPECIFICATIONS*	GP-1750HD	GP-3000HD	GP-5000HD
Continuous Output Power	1750 W (VA)	3000 W (VA)	5000 W (VA)
Maximum Surge Rating	3500 W (VA)	6000 W (VA)	10000 W (VA)
Output Waveform	Modified Sine Wave		
Output Voltage Range	100 - 120 VAC RMS +5/-15		
Input Voltage	10.5 - 16 VDC		
Efficiency	≥80%	≥85%	≥80%
No Load Current Draw	≤1 A	≤1.2 A	≤1.2 A
USB Output	4.75 - 5.25 VDC / 2.1 A		
Protection	Overload, Over Temperature, Over/Under Voltage, Short Circuit		
Low Battery Alarm ± 0.5 V	10.5 V		
Low Battery Shutdown ± 0.5 V	10 V		
Operating Temperature Range	32°F - 104°F (0°C - 40°C)		
Storage Temperature Range	14°F - 122°F (-10°C - 50°C)		
Cooling	Thermostatically Controlled Fan		
AC Output Connections	3 Standard North American Outlets	4 Standard North American Outlets	
Remote Power Option	Yes		
Dimensions (L x W x H)	8.07" x 8.86" x 3.50" (205 mm x 225 mm x 89 mm)	11.41" x 9.92" x 4.13" (290 mm x 252 mm x 105 mm)	18.50" x 9.92" x 4.13" (470 mm x 252 mm x 105 mm)
Weight	6.42 lbs (2.91 kg)	10.54 lbs (4.78 kg)	15.65 lbs (7.10 kg)
Warranty	1 Year		
Inverter Install Kits (sold separately)	GP-DC-KIT3	GP-DC-KIT5	
Remotes (sold separately)	GP-HD-R		

*Specifications subject to change without notice

PROTECT YOURSELF AND YOUR EQUIPMENT.

FUSE AND CABLE KITS

Go Power! DC installation kits include everything you need to properly connect your Go Power! inverter to the batteries safely. The kit includes 10' large gauge battery cables, tie downs, lugs, and the appropriate inverter fuse (class T fuse) and mounting block.



12 VOLT	INVERTER SIZE
GP-DC-KIT 2	600-1000 W
GP-DC-KIT 3	1100-1800 W
GP-DC-KIT 4	2000-2500 W
GP-DC-KIT 5	2600-3000 W

REMOTELY TURN YOUR INVERTER ON/OFF AND SAVE BATTERY POWER.

INVERTER REMOTE

Remotely power appliances or electronics with the compact Go Power! inverter remote. The remote features an LED indicator showing inverter status, an ON/OFF switch and 25' of cable.



Specifications may be subject to change. Product may not be exactly as shown. Specifications subject to local environmental conditions.



P: +1 866 247 6527
E: sales@gopowersolar.com
W: gopowersolar.com

201 - 710 Redbrick St,
Victoria, British Columbia,
Canada, V8T 5J3